

(18)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

**0 085 975
B1**

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 18.10.89

(51) Int. Cl.⁴: G 06 K 15/00, G 07 C 3/00

(21) Application number: 83101138.2

(22) Date of filing: 07.02.83

(54) History information providing device for printers.

(30) Priority: 08.02.82 JP 17480/82

(43) Date of publication of application:
17.08.83 Bulletin 83/33

(45) Publication of the grant of the patent:
18.10.89 Bulletin 89/42

(84) Designated Contracting States:
DE FR IT

(56) References cited:
EP-A-0 002 567
US-A-3 704 363
US-A-4 133 477
US-A-4 290 138

(73) Proprietor: Hitachi, Ltd.
5-1, Marunouchi 1-chome
Chiyoda-ku Tokyo 100 (JP)

(72) Inventor: Tadokoro, Hiroyuki
Sakuragawaryo 1-3 Kokubucho-2-chome
Hitachi-shi (JP)

(74) Representative: Altenburg, Udo, Dipl.-Phys.
et al
Patent- und Rechtsanwälte Bardehle-
Pagenberg-Dost-Altenburg & Partner Postfach
86 06 20
D-8000 München 86 (DE)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European patent convention).

Courier Press, Leamington Spa, England.

EP 0 085 975 B1

Description

This invention relates to printers and in particular to a history information providing device suitable for maintenance and inspection of the printers.

Conventionally, various kinds of printers have been utilized and maintenance and inspection have been a serious problem common to such various kinds of printers. This is because the mechanical operation cost of semi-automatic machines such as printers may include maintenance cost as a major part thereof and therefore means or procedure to reduce time required for the maintenance/inspection is advantageous in reduction in such mechanical operation cost.

To reduce time required for the maintenance/inspection of a printer, it is advantageous to utilize the history information of the printer, the kind of which is briefly classified as follows:

(1) Failure Information: for example, paper jam; and

(2) Maintenance Information: for example, worn condition.

How to recognize such history information is an important matter for an operator, user or service man of a printer.

In the conventional printers, as the maintenance information, the total number of printed paper has been displayed by display means such as an accumulated paper number counter or an alpha-numerical display tube. The necessity of separate provision of such display means has caused a problem in limitation of space and has been disadvantageous in cost reduction.

Further, with respect to failure or fault information, the recognition of such failure information in history form has, to the best of our knowledge, only been achieved in one prior art printer as acknowledged hereinafter. It has not been attained in the remaining printers because non-volatile memories for faults have not been employed in the other printers. Although failure information could be recognized when it occurred, the failure information was refreshed or cleared upon the recovery of the failure, so that there was a problem in that the history information as to failures or faults of printers could not be recognized and this made it difficult to attain proper maintenance and repair of the printers.

The printer that is the exception is the one disclosed in EP-A-2 567. During operation of the machine fault conditions are logged into a non-volatile digital store. To diagnose errors, a scan of the store is made to retrieve the logged fault conditions and these are made available on a digital display. Such a digital display device does, of course, increase the manufacturing costs of the printer and this is naturally a disadvantage.

Another prior art document is US-A-3,704,363 that is concerned with a statistical data logging apparatus, for example of the kind having rotating disc storage drives. The object is to try to identify, when stored information is being transferred, whether errors in the information trans-

ferred is due to errors in the disc packs themselves or the drives associated with the disc packs. The apparatus is intended to assist in sorting out the one type of error from the other over a period and on occasions to make a print out of the information obtained. For this purpose a printing means is coupled to the statistical data logging device.

An object of the present invention is therefore, to provide a history information providing device for a printer in which the latest (updated) history information required for maintenance/inspection of the printer can be effectively acquainted to the service engineer when maintenance/inspection is to be performed without relying on the use of a digital display to communicate the history information to the service engineer.

In accordance with the broadest concept of the present invention the latest history information for maintenance/inspection of a printer is, in a non-volatile fashion, stored in the printer per se on the basis of the information detected by various sensors, so that when required, the latest information is not displayed by a digital display means such as, for example, an alpha-numerical tube but printed out by the printer per se owing to its own printing ability.

According to the present invention there is provided a history information providing device for a printer having a print producing section provided with information pick-up means for detecting printing operations and having a programmable control section for controlling said print producing section, said history information providing device comprising:

a non-volatile memory provided in said programmable control section for storing the latest failure and/or maintenance information relating to said print producing section and picked up by said information pick-up means; characterized in that:—

said history information providing device for the printer comprises print-out instructing means for producing a print-out instruction, and said programmable control section is responsive to an instruction from said print-out instructing means to cause said print producing section, whilst the printer is in working order or upon completion of failure repair, to print out printer history information stored in said non-volatile memory, said printer history information including at least a part of the latest failure and/or maintenance information and self-diagnosis information obtained on the basis of said latest failure and/or maintenance information.

According to the above-mentioned arrangement, the history information output device for a printer can acquaint an operator or user, when required, with the latest history information required for maintenance/inspection of the printer in an obvious form to thereby make it possible to expect the improvement in the efficiency of the maintenance/inspection operation and in the maintenance cost reduction.

Preferred embodiment means of the invention

will be described by referring to the accompanying drawings, in which:

Fig. 1 is a schematic diagram of a laser beam printer which employs transfer type electrophotographic processing (xerographic processing) and which is a type of printers to which the present invention is applied;

Fig. 2 is a block diagram illustrating the configuration of the printer according to an embodiment of the present invention;

Fig. 3A is a schematic block diagram of the non-volatile memory in the embodiment of Fig. 2;

Figs. 3B to 3D are circuit diagrams illustrating examples of the non-volatile memory constituted by a battery backed up random access memory (RAM);

Fig. 3E is a circuit diagram illustrating the print-instructing circuit in Fig. 2;

Fig. 4 is a diagram illustrating allocation of the working areas in the static read-only memory (ROM) in Fig. 3A; and

Figs. 5 to 8 are flowcharts of operations in the above-mentioned embodiment.

Prior to the description of embodiments of the present invention, description will be made, referring to Fig. 1, with respect to a laser beam printer which employs transfer type electrophotographic processing (xerographic processing) and which is a type of printers to which the present invention is applied.

In Fig. 1, a laser beam printer 10 is provided with a photoconductive drum 20 which rotates in the direction shown by an arrow and passes by a plurality of xerographic processing stations.

Provided in the first xerographic processing station is a charger 21 for projecting positive or negative charges onto the surface of the photoconductive drum 20. Preferably, the charger 21 may uniformly project electrostatic charges. The charging is performed under the condition that there is no light such as optical image projection so that an exposing light, such as a laser beam 22 shown by a one-dotted chain line arrow, may change the distribution of charges on the surface of the photoconductive drum 20 to thereby prepare for the image developing and transferring operations.

The laser beam 22 emitted from a laser optical device 23 is subjected to pulse-modulation by a controller 11 and caused, by a deflection mirror driving motor (not shown) provided in the laser optical device 23, to scan the photoconductive drum 20 in the axial direction thereof. Since the photoconductive drum 20 is rotated in the direction as shown by the arrow, an electrostatic image, namely a latent image, is produced in the surface of the photoconductive drum 20.

In the next xerographic processing station provided is a developer 24 which receives toner particles from a toner supply source 25 and applies the toner particles to surface portions of the drum 20 at which charges still remain. In particular, the polarity of the toner particles forwarded to the developer 24 from the toner supply source 25 is selected to be opposite to that of the

charges on the surface of the photoconductive drum 20. Accordingly, the toner particles may attach to the charged portions and do not attach to the non-charged portions at which the laser beam has been irradiated. Thus, the photoconductive drum 20 which has passed by the developer 24 bears a developed image corresponding to the signal modulated by the controller 11. The toner particles on the latent image is transferred to a sheet of print paper in the next xerographic station at which a transfer device 26 is provided. The print paper is fed along a paper path 29 and through a synchronizing gate 28 from a paper cassette 27 to the transfer device 26. At this xerographic station, the print paper is made in contact with the developed image on the surface of the photoconductive drum 20 so that the toner particles on this image may be transferred onto the paper.

Upon the completion of transfer, the image bearing print paper is separated from the surface of the photoconductive drum 20 and caused to advance along a succeeding paper path 30.

At the next xerographic station where a fixer 31 in the form of a thermal roller is provided, the toner particles on the print paper is fixed thereto so as to provide a fixed image on the print paper.

Then, the print paper is discharged into a discharge tray 32.

Turning back to the photoconductive drum 20, a considerable amount of toner particles remain on the surface of the drum 20 even after the drum 20 has passed by the transfer device 26. Accordingly, the remaining charges on the surface of the photoconductive drum 20 are neutralized by a discharger 33 in the next xerographic station so that the neutralized toner particles are removed from the drum surface by a cleaner 34 at the next but one station. Thus, one printing cycle has been completed.

The laser beam printer 10 is provided with further means as follows other than the above-mentioned xerographic processing means.

There are provided, as paper jam detecting means, a first and a second paper passage detecting sensors 35 and 36 on the paper paths 29 and 30, respectively.

Since various kinds of print papers are used, it is necessary to adjust the timing of xerography sequence to correspond to the length of paper in the travelling direction thereof. To this end, there is provided a paper size sensor 37 for automatically detecting the size of paper.

Thus, the print producing section of the printer 10 is constituted by the photoconductive drum 20, the charger 21, the laser optical device 23, the developer 24, the toner supply source 25, the transfer device 26, the paper cassette 27, the synchronizing gate 28, the fixer 31, the paper discharge tray 32, the discharger 33, and the cleaner 34. The controller 11 which constitutes the main control section of the printer 10 may be those disclosed in Braham U.S. Patent No. 4,046,471 issued September 6, 1977 and Gunning U.S. Patent No. 4,169,275 issued September 25,

1979, each relating to control techniques for laser scanning xerographic printers.

Referring to the drawings, an embodiment of the present invention will now be described. The embodiment relates, by way of example, to a laser beam printer utilizing the xerographic processing as mentioned above.

Fig. 2 is a block diagram illustrating the basic configuration of the printer according to the present invention. In Fig. 2, reference numerals 10 and 11 denote the same laser beam printer and controller as those shown in Fig. 1, respectively.

The controller 11 is constituted, as shown in Fig. 2, by a main control circuit 100 which includes a xerographic sequencer 101 for performing the above-mentioned xerography processing and a laser beam modulated signal processor 102 provided with such as a 64 KB (kilobytes) RAM, a non-volatile memory 111 into which the latest history information on the printer mechanisms is written from the main control circuit 100 and from which it is read out when required, and a print-out instructing circuit 112 for instructing a commande to the main control circuit 100 when the latest history information is required to be printed out.

Basically, the main control circuit 100 may be those disclosed in the above-mentioned two U.S. Patents and receives inner condition signals from a group of sensors 103 and external signals from input means 140. The sensor group 103 includes the first and second paper passage detecting sensors 35 and 36 for detecting paper jam, the paper size detecting sensor 37, which are the same as those described above with respect to Fig. 1, and a ready state sensor (not shown) for detecting the ready state of the fixer 31. Since the fixer 31 is in the form of a thermal roller, it is preheated in use until it has reached the temperature at which fixing can be attained and then it is controlled to be maintained within a proper temperature region. To this end, the temperature of the fixer 31 is detected by a temperature sensor (not shown) and subjected to feed-back control. The ready state sensor detects the ready state of the thermal fixer 31. The input means 140 is responsive to a host CPU which handles the printer 10 as its terminal device so as to apply output alpha-numerical data signals, data print request signals, etc. to the main control circuit 100. That is, for example, upon the receipt of the data print request signal, the main control circuit 100 applies control signals to the respective devices provided in the print producing section of the laser beam printer 10 so as to cause the devices to perform the xerographic processing. Further, in Fig. 2, output means 150 may include the above-mentioned devices 20 to 34 which are, for example, the type system, the paper feed system, the laser exposing system and which are on-off controlled in synchronism with the rotation of the drum 20 of the printer.

Fig. 3A shows a block diagram illustrating the basic configuration of the above-mentioned non-volatile memory 111.

In Fig. 3A a chip selection signal \overline{CS} and a write

enable signal \overline{WE} are applied from the main control circuit 100 to the non-volatile memory 111. When the signal \overline{CS} is at its low level (hereinafter simply referred to as LOW), the non-volatile memory 111 is in its activated state in which it becomes externally accessible and in addition when the signal \overline{WE} is LOW, an input three-state buffer 120 is made activated so that input/output devices I/O₁ to I/O₄ are made available in the input port of the non-volatile memory 111.

When the signal \overline{WE} is in its high level (hereinafter referred to as HIGH), an output three-state buffer 121 is made activated so that the I/O₁—I/O₄ are made available in the output port of the non-volatile memory 111.

Address signals A₀—A₂ from the main control circuit 100 designate the row addresses of a static RAM (random access memory) 125 through a row selecting circuit 123 and a row instructing circuit 124, while address signals A₃—A₅ from the main control circuit 100 designate the column addresses of the RAM 125 through a column selecting circuit 126 and a column instructing and input/output circuit 127.

The writing operation into the static RAM 125 will be now described.

First, both the signals \overline{CO} and \overline{WE} are set to be LOW. Signals from the I/O₁—I/O₄ are then applied to an input data control circuit 128 through the input three-state buffer 120. The column instructing and input/output circuit 127 is controlled on a time division basis and transfers the output of the input data control circuit 128 to the static RAM 125 after the column designation. Thus, the output signals from the I/O₁—I/O₄, which are now operating as the input port of the non-volatile memory 111, have been written into the static RAM 125.

When the contents are read out of the static RAM 125, on the other hand, the signal \overline{WE} is made HIGH so that the output signals are transferred from the static RAM 125 to the I/O₁—I/O₄, which are now operating as the output port of the non-volatile memory 111, through the column instructing and input/output circuit 127 and the output three-state buffer 121.

A decoder 129 controls the data transfer between the static RAM 125 and an E²PROM (electrically erasable programmable read only memory) 130. The E²PROM 130 may be X2210 available on the market. That is, upon the turning-on of the power supply, the decoder 129 instructs the E²PROM 130 and the static RAM 125 to transfer data from the former to the latter in response to a signal \overline{RECALL} applied from e.g. the main control circuit 100, while when the power supply is turned off, it instructs them to transfer data from the latter to the former in response to a signal \overline{STORE} applied from e.g. the main control circuit 100. The static RAM 125 and the E²PROM 130 are arranged such that they correspond to each other in a one-to-one bit relation.

As shown in Fig. 3B, the main control circuit 100 and the non-volatile memory 111 are constituted by a single-chip CMOS MCU (complementary

metal oxide semiconductor microcomputer unit) which includes ROM, RAM, CPU, ACI (serial interface) and which may be the type HD 6303 of HITACHI. The MCU chip includes a battery backed-up RAM in place of E²PROM to provide the non-volatile store performance. Fig. 3C is a block diagram illustrating the configuration of the MCU HD 6303. In Fig. 3C, when the power supply Vcc is in its off-state, the whole circuit of the MCU chip is battery-backed up, while when the power supply is on, that is, when a signal applied to the MCU chip is HIGH, only the RAM 125 is battery-backed up. Fig. 3D shows an example of the configuration of the non-volatile memory 111 of the battery-backup type employing CMOS RAM IC which may be for example such as the type HM 6116 of HITACHI. In this IC configuration, with respect to the failure information and/or the maintenance information, only the number of times of events and the time elapsed from each event are stored in the non-volatile memory 111. Seven bytes A₀—A₆ are connected to an address bus and eight bits D₀—D₇ are connected to a data bus. The item format program for such information is stored in the main control circuit 100.

Fig. 3E shows an example of the print-out instructing circuit 112 which employs a known maintenance switch SW_M to supply the main control circuit 100 with instructions of reading information out of the non-volatile memory and performing print-out operation. A ten key SW_T supplies the main control circuit 100 with an instruction or predetermined key code so that only the specified part of the stored information can be read out. When the maintenance switch SW_M is on, the laser power and the printing process timings are adjusted and the paper jam counting and the history information storing are reset or cleared.

Turning to Fig. 3A, the static RAM 125 is used to provide a working area for the latest history information required for maintenance/inspection. Fig. 4 shows the allocation of the working area of the static RAM 125. In the drawing, ADDRESS denotes the addresses \$00, \$20 and \$3F, CONTENTS denotes the contents of stored information, WRITE denotes the portion to be controlled in writing and READ denotes the part from which reading is performed. The contents of the working area allocation will be now described.

In the laser beam printer 10, the following information is required for the user when maintenance/inspection is performed;

(1) The total number of printed paper, which has been conventionally counted by an accumulated sheet-number counter or the like, as the latest information for controlling the service life of the photoconductive drum 20, the developing agents, etc.;

(2) The total number of printed paper by paper sizes for obtaining information with respect to the state of used print paper; and

(3) The total operated time of a deflection mirror driving motor for governing the life of the deflection mirror driving motor. On the assump-

tion that the deflection mirror driving motor operates for a predetermined time for one sheet of print paper, the total operated time of the deflection mirror driving motor may be obtained by multiplying the total number of printed paper by the above-mentioned predetermined time.

The above-mentioned maintenance information is mainly required for the user and therefore the printer is arranged such that the print-out of the latest maintenance information may be performed by merely pressing down a separately provided push button with no help by a person of the dealer side. The maintenance information is updated by the instruction from the main control circuit 100 in accordance with the operation flow which will be described later.

As the latest history information which is required for maintenance/inspection and which requires the help by the dealer, it is advantageous to obtain the latest failure information as follows other than the latest maintenance information as mentioned above;

(1) The total number of times of paper jam which has been detected by the main control circuit 100 by judging the input timings of the first and second paper passage detecting sensors 35 and 36 in the laser beam printer 10;

(2) The total number of times of paper jam by places of jam occurrence and by paper passage detecting sensors (when two or more sensors are provided; and

(3) The total number of times of paper jam by paper sizes;

(4) The total number of times of toner supply by the toner supply source.

The above-mentioned latest failure information may be an important information source which may acquaint the dealer or service man, who is not always present by the laser beam printer 10 when the printer is operated, with the state of actual operation of the printer 10.

With respect to the utilization of the latest failure information, the printer is arranged such that only a service man or the like dispatched by the dealer can produce the instruction of print-out of the latest failure information by actuating a push-button provided for private use for the service man or by the predetermined key code input as shown in Fig. 3E, at the time of periodical inspection or checking or upon the completion of failure repair. The latest failure information is renewed by the instruction from the main control circuit 100 in accordance with the operation flow which will be described later.

Referring to Figs. 5 to 8, the above-mentioned operation flow will be described.

In Fig. 5, upon turning the power on, the data with respect to the CONTENTS in Fig. 4 stored in E²PROM 130 of the non-volatile memory 111 is written into the static RAM 125 in the step 200 and then the operation state goes into the ready mode. Next, in the step 201, the power is judged whether it is in its off-state or not, and when it is in its off-state, the operation state shifts into the end mode, while if not so, the operation state goes

into the step 202 in which detection is made as to whether a maintenance instruction from the print-out instructing circuit 112 is present or not.

When there exists a maintenance instruction, the operation state goes into the maintenance mode, while if not so, it goes into the step 203 in which detection is made as to whether there exists a print request from the input means 140.

When there exists no print request, the operation state returns into the ready mode again, while if the print request exists, it goes into the step 204 in which detection is made as to whether any failure such as paper jam exists or not. When there exists any failure or fault, the operation state goes into the failure mode, while if not so, it goes into the step 205. In the step 205, the operation state traces the loop to return to the print mode as shown in Fig. 5 until the printing operation has been completed through the above-mentioned xerographic processing. Upon the completion of the printing operation, the operation state goes into the step 206 in which the data of the latest maintenance information stored in the static RAM 125, such as the total number of printed paper, the total number of printed paper in each paper size, the total amount of operated time of the deflection mirror driving motor, is renewed by incrementing through the counter the number of times of the concerned events and the operation state returns then into the ready mode again.

Referring to Fig. 6, the end mode will be now described. When the operation state has shifted from the step 201 of Fig. 5 into the end mode of Fig. 6, the above-mentioned data stored in the static RAM 125 of the non-volatile memory 111 are transferred to the E²PROM to be stored therein in the step 207 of Fig. 6 and then the operation terminates.

Referring to Fig. 7, the failure mode is described. When the operation state has shifted from the step 204 of Fig. 5 to the failure mode, the data of the latest failure information stored in the static RAM 125 are renewed in the step 208 of Fig. 7. In case of a failure or fault, since the power supply to the non-volatile memory 111 and the main control memory 100 is maintained as it was, while the power supply to the output means 150 in which there are dangers of causing electrical shocks from a high potential source therein is cut off, it is possible to reliably renew the data of the latest failure information. Then, upon the completion of repair of the failure through off-line processing by the manual operation by any operator or service man, the failure flag is erased and the operation state returns to the ready mode again so as to enable the print-out to be performed. By the way, the non-volatile memory 111 is maintained in its activated state even during a failure.

Referring to Fig. 8, the maintenance mode will be described. When the operation state has shifted into the maintenance mode in the step 202 of Fig. 5, the necessary data of the latest history information in the static RAM 125 is fetched into the laser beam modulated signal processor 102 in

the main control circuit 100 in the step 210. Then, in the step 211, the necessary data of the latest history information is printed out through the xerographic processing by the laser beam printer 10. Upon the completion of the print-out, the operation state returns into the ready mode again.

By the way, the amount of the latest history information required by the dealer or service man is more than that required by the user. In this regard, the print-out instructing circuit 112 may be arranged such that it produces instruction signals for the user as well as the dealer. However, the detail of the arrangement is not described here in conjunction with the embodiment.

Further, the latest history information may include not only the latest maintenance information and the latest failure information as mentioned above but the secondary or succeeding information, such as the rate of paper jam, the rate of paper jam in each paper size, the frequency or rate of the toner supply, the extent of waste of wasting members, which is obtained by arithmetic operations in the main control circuit 100 on the basis of the above-mentioned latest maintenance and failure information data. The paper jam rate is determined by the ratio of the number of times of paper jam to the total number of printed paper. With respect to the total number of printed paper, there is a case where the total number of printed paper is counted from the initiation of operation of the printer and another case where it is counted from the initiation of every service interval after a service man has reset or cleared the total number of printed paper incremented so far. The toner supply rate is obtained by calculating the number of toner supply times by service intervals by counting the r.p.m. of the toner supply motor. The basic configuration of toner controller including the developer 24 and the toner source 25 is disclosed in U.S. Patent No. 3,572,551 issued March 30, 1971 to Gillespie et al.

As described above, according to the embodiment of the present invention, the latest history information for maintenance/inspection of a laser beam printer can be obtained in an obvious form by printing it out by the printer, resulting in advantages in that the maintenance/inspection of printer can be easily performed and the cost of maintenance can be therefore remarkably reduced. Further, the efficiency in working of maintenance/inspection is also remarkably improved.

Further, since the latest history information is directly printed out and produced in the form of a printed data, there is no need of providing any display means such as an alpha-numerical display device, resulting in improvements in reliability and in the reduction of the cost from an economical point of view.

Further, also from the dealer's standpoint, it becomes possible to follow up the failure, such as paper jam, at the periodical inspection or upon

the completion of repair of failure so as to obtain strong data on the market of products, resulting in improvement in reliability. Further, in the case where paper jam has frequently occurred in the same position, it is possible to immediately effect proper adjustment when a service man is dispatched, resulting in reduction in the time required for maintenance/inspection.

As another embodiment, a battery-backup RAM may be used as the non-volatile memory 111 with the same effect.

The renewal of the contents of the static RAM 125 as described above in the first-mentioned embodiment may be performed by counting up (incrementing) from the initial value which is reset to be zero or counting down from (decrementing) the initial value which is set to a predetermined value.

Further, the print-out instructing circuit 112 for producing instruction signals as described above in the first-mentioned embodiment may be arranged such that the instruction signal is generated in response to a forced external signal produced by the operator, for example, by depressing a push button, or, alternatively, the main control circuit 100 in the controller 11 effects self-diagnosis by comparing the latest history information stored in the non-volatile memory 111, e.g. the latest maintenance information relating to the total number of printed paper, with a previously set maintenance condition, e.g. a preset number of paper to be printed so that when the actually printed paper number exceeds the preset value, the main control circuit 100 automatically produces a signal, in response to which the print-out instructing circuit 112 generates the print-out instruction signal to print out the result of self-diagnosis for user's or dealer's information and warning. In the latter arrangement in which self-diagnosis is effected, the setting value of the number of paper to be printed may be stored in the main control circuit 100 as one of the maintenance conditions and a comparator circuit function (not shown) is provided in the main control circuit 100 for comparing the latest number of the printed paper with the setting number of paper to be printed so as to automatically produce a signal on the basis of the result of comparison.

Claims

1. A history information providing device for a printer having a print producing section (10) provided with information pick-up means (35—37; 103) for detecting printing operations and having a programmable control section (11) for controlling said print producing section, said history information providing device comprising:

a non-volatile memory (111) provided in said programmable control section for storing the latest failure and/or maintenance information relating to said print producing section and picked up by said information pick-up means; characterized in that:—

said history information providing device for

the printer comprises print-out instructing means (112) for producing a print-out instruction, and said programmable control section (11) is responsive to an instruction, from said print-out instructing means (112), to cause said print producing section (10), whilst the printer is in working order or upon completion of failure repair, to print out printer history information stored in said non-volatile memory (111), said printer history information including at least a part of the latest failure and/or maintenance information and self-diagnosis information obtained on the basis of said latest failure and/or maintenance information.

2. A history information providing device according to Claim 1, in which said print-out instructing means includes input means for freely inputting a print-out instruction by an operator of said printer in accordance with a requirement by the operator.

3. A history information providing device according to Claim 1, in which said print-out instructing means includes means for comparing the latest maintenance with a preset maintenance condition to effect self-diagnosis so as to produce said print-out instruction when said latest maintenance information exceeds said preset maintenance condition.

4. A history information providing device according to Claim 1, in which said non-volatile memory (111) includes a static random access memory (RAM) (125) and a non-volatile electrically erasable programmable read only memory (E²PROM) which corresponds to said static RAM in a one-to-one bit relation, said static RAM and said non-volatile E²PROM being arranged so that when a power source is turned off, the contents of said static RAM at the instant are transferred to said E²PROM.

5. A history information providing device according to Claim 1, in which said non-volatile memory (111) includes a battery backed-up static RAM.

6. A history information output device according to Claim 2, in which said input means includes a manually actuatable switch for enabling said print producing section to print out only a selected part of said latest history information.

7. A history information providing device according to Claim 2, in which said input means includes a password sequence circuit for producing said print-out instruction in response to a predetermined key code applied thereto by the operator.

8. A history information providing device according to Claim 1, in which means for accumulating the number of times of events is connected between said information pick-up means and said non-volatile memory so that every time failure information and/or maintenance information is picked up by said information pick-up means, the number of times of the event relating to the picked-up failure and/or maintenance information is incremented.

9. A history information providing device according to Claim 1, in which said non-volatile

memory (111) is written-in by a main control circuit (100) provided in said control section (11) and read out by said print-out instructing means (112), a working area of said non-volatile memory being provided with a first place for storing therein maintenance information including at least one of the total number of printed paper, the total number of printed paper by paper sizes and the total operated time of a deflection mirror driving motor, and a second place for storing therein failure information including at least one of the total number of times of paper jam, the total number of times of paper jam by paper jam occurring places, the total number of times of paper jam by paper sizes and the total number of times of toner supply.

10. A history information providing device according to Claim 9, in which said print-out instructing means causes said main control circuit to read out the maintenance and/or failure information stored in said non-volatile memory and calculate history information including at least one of a rate of paper jam, a rate of paper jam by paper sizes, a rate of toner supply and an extent of waste of wasting members on the basis of the read-out information so that a selected part of said history information can be printed out.

Patentansprüche

1. Vorrichtung zum Liefern von Betriebsablaufdaten für einen Drucker mit einer druckerzeugenden Einheit (10), die mit einer Informationsaufnahme-einrichtung (35-37; 103) zum Detektieren von Druckoperationen versehen ist, und mit einer programmierbaren Steuereinheit (11) zum Steuern der druckerzeugenden Einheit, wobei die Vorrichtung zum Liefern von Betriebsablaufdaten aufweist:

einen nicht-flüchtigen Speicher (111), der in der programmierbaren Steuereinheit zum Steuern des letzten Fehlers und/oder einer Wartungsinformation vorgesehen ist, die der druckerzeugenden Einheit zugeordnet ist und von der Informationsaufnahme-einrichtung aufgenommen wird;

dadurch gekennzeichnet,

daß die Vorrichtung zum Liefern von Betriebsablaufdaten für den Drucker aufweist

eine Ausdruckbefehlseinrichtung (112) zum Erzeugen eines Ausdruckbefehls, wobei die programmierbare Steuereinheit (11) auf einen Befehl von der Ausdruckbefehlseinrichtung (112) antwortet, um die druckerzeugende Einheit (10) dazu zu veranlassen, während der Drucker im Betriebszustand oder beim Beenden einer Fehlerbehebung ist, Betriebsablaufdaten des Druckers, die in dem nicht-flüchtigen Speicher (111) gespeichert sind, auszudrucken, wobei die Betriebsablaufdaten des Druckers mindestens einen Teil der letzten Fehler- und/oder Wartungsinformation und Selbstdiagnoseinformation umfassen, die aufgrund der letzten Fehler- und/oder Wartungsinformation erhalten wird.

2. Vorrichtung zum Liefern von Betriebsablaufdaten gemäß Anspruch 1, dadurch gekennzeichnet,

daß die Ausdruckbefehlseinrichtung eine Eingabeeinrichtung zum freien Eingeben eines Ausdruckbefehls durch einen Operator des Druckers in Übereinstimmung mit einer Anforderung durch den Operator aufweist.

3. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 1, dadurch gekennzeichnet, daß die Ausdruckbefehlseinrichtung eine Einrichtung zum Vergleichen der letzten Wartung mit einem voreingestellten Wartungszustand aufweist, um eine Selbstdiagnose zu bewirken, so daß der Ausdruckbefehl erzeugt wird, wenn die letzte Wartungsinformation den voreingestellten Wartungszustand überschreitet.

4. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 1, dadurch gekennzeichnet, daß der nicht-flüchtige Speicher (111) einen statischen Speicher mit wahlfreiem Zugriff (RAM) (125) und einen nichtflüchtigen, elektrisch löschbaren, programmierbaren Nur-Lesespeicher (E²PROM) enthält, der dem statischen RAM in einer eins zu eins Bit-Relation entspricht, wobei der statische RAM und der nicht-flüchtige E²PROM so angeordnet sind, daß, wenn eine Versorgungsspannung ausgeschaltet wird, die Inhalte des statischen RAMs sofort zu dem E²PROM übertragen werden.

5. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 1, dadurch gekennzeichnet, daß der nicht-flüchtige Speicher (111) einen batteriegepufferten statischen RAM aufweist.

6. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 2, dadurch gekennzeichnet, daß die Eingabeeinrichtung einen manuell betätigbaren Schalter zum Inbetriebsetzen der druckerzeugenden Einheit enthält, um nur einen ausgewählten Teil der letzten Betriebsablaufinformation auszudrucken.

7. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 2, dadurch gekennzeichnet, daß die Eingabeeinrichtung eine Passwortfolgeschaltung zum Erzeugen des Ausdruckbefehls in Antwort auf einen vorbestimmten Schlüsselcode aufweist, der in diese vom Operator eingegeben wird.

8. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 1, dadurch gekennzeichnet, daß eine Einrichtung zum Addieren der Anzahl von Ereigniszeitpunkten zwischen der Informationsaufnahme-einrichtung und dem nicht-flüchtigen Speicher verbunden ist, so daß in jedem Zeitpunkt, in dem eine Fehlerinformation und/oder eine Wartungsinformation aufgenommen wird, von der Informationsaufnahme-einrichtung, die Anzahl der Ereigniszeitpunkte, die der aufgenommenen Fehler- und/oder Wartungsinformation zugeordnet sind, inkrementiert wird.

9. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 1, dadurch gekennzeichnet, daß der nicht-flüchtige Speicher (111) von einer Hauptsteuerschaltung (100) beschrieben wird, die in der Steuereinheit (11) vorgesehen ist, und von der Ausdruckbefehlseinrichtung (112) ausgelesen wird, wobei ein Betriebsbereich des nicht-flüchtigen Speichers versehen ist mit einem ersten Ort

zum Speichern von Wartungsinformation, die zumindest enthält die Gesamtanzahl des gedruckten Papiers, die Gesamtanzahl mit Bezug auf die Papiergröße oder die Gesamtbetriebszeit eines Antriebsmotors für einen Ablenkspiegel, und mit einem zweiten Ort zum Speichern von Fehlerinformation, die zumindest enthält die Gesamtanzahl von Papierstauereignissen, die Gesamtanzahl der Papierstauereignisse bezüglich der Orte, an denen die Papierstau auftritt, die Gesamtanzahl der Papierstauereignisse bezüglich der Papiergrößen oder die Gesamtanzahl der Zeitpunkte der Tonerzuführung.

10. Vorrichtung zum Liefern von Betriebsablaufdaten nach Anspruch 9, dadurch gekennzeichnet, daß die Ausdrucksbefehlseinrichtung die Hauptsteuerschaltung veranlaßt, die Wartungs- und/oder Fehlerinformation auszulesen, die in dem nicht-flüchtigen Speicher gespeichert ist, und die Betriebsablaufdaten zu berechnen, die zumindest enthält eine Papierstaurate, eine Papierstaurate bezüglich der Papiergrößen, eine Rate der Tonerzuführung oder ein Abnutzungsausmaß von sich abnutzenden Teilen, und zwar auf der Basis der ausgelesenen Information, so daß ein ausgewählter Teil der Betriebsablaufdaten ausgedruckt werden kann.

Revendications

1. Dispositif délivrant une information sur l'historique du fonctionnement d'une imprimante comportant une section (10) de production d'impressions, équipée de moyens (35-37; 103) de détection d'informations, servant à détecter des opérations d'impression et comportant une section de commande programmable (11) servant à commander ladite section de production d'impressions, ledit dispositif délivrant une information de l'historique de fonctionnement incluant:

une mémoire rémanente (111) prévue dans ladite section de commande programmable pour mémoriser la dernière information de panne et/ou de maintenance concernant ladite section de production d'impressions et détectée par lesdits moyens de détection d'informations;

caractérisé en ce que:

ledit dispositif délivrant une information sur l'historique de fonctionnement de l'imprimante comporte des moyens de commande d'impression (112) servant à produire une instruction d'impression, et ladite section de commande programmable (11) est sensible à une instruction délivrée par lesdits moyens de commande d'impression (112) pour amener ladite section de production d'impressions (10), alors que l'imprimante est prête à fonctionner ou lors de l'achèvement de l'élimination d'une panne, à imprimer l'information concernant l'historique de fonctionnement de l'imprimante, mémorisée dans ladite mémoire rémanente (111), ladite information de l'historique de fonctionnement de l'imprimante comprenant au moins une partie de l'information du dernier défaut et/ou de la dernière maintenance et une information d'auto-diagnostic obtenue

sur la base de ladite information de la dernière panne et/ou maintenance.

2. Dispositif délivrant une information d'historique selon la revendication 1, dans lequel lesdits moyens de commande d'impression incluent des moyens d'entrée permettant la libre introduction d'une instruction d'impression par un opérateur faisant fonctionner ladite imprimante, conformément à une exigence de l'opérateur.

3. Dispositif délivrant une information d'historique selon la revendication 1, dans lequel lesdits moyens de commande d'impression incluent des moyens pour comparer la dernière maintenance à une condition de maintenance préétablie de manière à réaliser un auto-diagnostic afin de délivrer ladite instruction d'impression lorsque ladite dernière information de maintenance dépasse ladite condition de maintenance préétablie.

4. Dispositif délivrant une information d'historique selon la revendication 1, dans lequel ladite mémoire rémanente (111) comporte une mémoire à accès direct statique (RAM) (125) et une mémoire morte programmable rémanente effaçable électriquement (E²PROM), qui correspond à ladite mémoire RAM statique selon une relation biunivoque, ladite mémoire RAM statique et ladite mémoire rémanente (E²PROM) étant agencées de telle sorte que, lors de l'interruption d'une source d'alimentation en énergie, le contenu de ladite mémoire RAM statique à cet instant est transféré dans ladite mémoire E²PROM.

5. Dispositif délivrant une information d'historique selon la revendication 1, dans lequel ladite mémoire rémanente (111) comporte une mémoire RAM statique protégée par batterie.

6. Dispositif délivrant une information d'historique selon la revendication 2, dans lequel lesdits moyens d'entrée incluent un interrupteur pouvant être actionné manuellement et permettant de valider ladite section de production d'impressions pour qu'elle fournisse une sortie imprimée uniquement d'une partie sélectionnée de ladite dernière information d'historique.

7. Dispositif délivrant une information d'historique selon la revendication 2, selon lequel lesdits moyens d'entrée incluent un circuit séquentiel à mot de passe servant à délivrer ladite instruction d'impression en réponse à un code prédéterminé, qui lui est appliqué par l'opérateur.

8. Dispositif délivrant une information d'historique, selon la revendication 1, dans lequel des moyens servant à cumuler le nombre d'apparitions d'événements sont branchés entre lesdits moyens de détection d'informations et ladite mémoire rémanente de sorte que chaque fois qu'une information de panne ou une information de maintenance est détectée par lesdits moyens de détection d'informations, le nombre d'apparitions de l'événement concernant l'information détectée de panne et/ou de maintenance est incrémenté.

9. Dispositif délivrant une information d'historique selon la revendication 1, dans lequel l'enre-

gistrement à l'intérieur de ladite mémoire rémanente (111) est réalisé au moyen d'un circuit principal de commande (100) prévu dans ladite section de commande (11) et est lu par lesdits moyens de commande d'impression (112), une zone de travail de ladite mémoire rémanente comportant un premier emplacement pour y mémoriser une information de maintenance incluant au moins une feuille faisant partie du nombre total de feuilles imprimées, le nombre total de feuilles imprimées pour les tailles des feuilles et le temps de fonctionnement global d'un moteur d'entraînement du miroir déviateur, et un second emplacement servant à mémoriser une information de panne incluant au moins un blocage parmi le nombre total de blocages du papier, le nombre total de blocages du papier pour les différents emplacements d'apparition de blo-

cages du papier, le nombre total de blocages du papier pour les tailles de papier et le nombre total de délivrances de toner.

10. Dispositif délivrant une information d'historique selon la revendication 9, dans lequel lesdits moyens de commande d'impression amènent ledit circuit principal de commande à lire l'information de maintenance et/ou de panne mémorisée dans ladite mémoire rémanente et à calculer une information d'historique incluant au moins un blocage parmi le nombre de blocages du papier, une fréquence des blocages du papier pour les tailles de papier, une fréquence d'alimentation du toner et la quantité perdue d'éléments gaspillés, sur la base de l'information de lecture de sorte qu'une partie sélectionnée de ladite information d'historique peut être imprimée.

20

25

30

35

40

45

50

55

60

65

10

LASER BEAM PRINTER 10




FIG. 2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 4

(ADDRESS)	(CONTENTS)	(WRITE)	(READ)
\$ 00	TOTAL NUMBER OF PRINTED PAPER	MAIN CONTROL CIRCUIT	PRINT-OUT INSTRUCTION CIRCUIT (FOR USER)
FOR USER MAINTENANCE INFORMATION	NUMBER OF PRINTED PAPER BY PAPER SIZES		
	TOTAL OPERATED TIME OF DEFLECTION MIRROR DRIVING MOTOR		
\$ 20	TOTAL NUMBER OF TIMES OF PAPER JAM	MAIN CONTROL CIRCUIT	PRINT-OUT INSTRUCTION CIRCUIT (FOR SERVICE MAN)
FOR DEALER	NUMBER OF TIMES OF PAPER JAM OF PLACES (BY SENSORS)		
FAILURE INFORMATION	NUMBER OF TIMES OF PAPER JAM		
	NUMBER OF TIMES OF TONER SUPPLY		
\$ 3F			




FIG. 6




FIG. 7




FIG. 8

